

CT-FSK-07 | 3-50AK CW premium



PROFESSIONAL CW COLD WEATHER SELF-ADHESIVE FOIL SCRIM KRAFT TAPE

FEATURES:

- ◆ Premium cold weather acrylic adhesive
- ◆ Good water vapor resistance
- ◆ Premium silicone kraft liner

POSSIBLE APPLICATIONS:

- ◆ To seal joints of insulation facing in duct fabrication, ventilation, refrigeration and construction industry



	<ul style="list-style-type: none"> ◆ Soft aluminum foil ◆ 3-directional Fiberglass Scrim /Kraft paper ◆ Solvent-based cold weather acrylic adhesive ◆ Silicone release kraft liner 		
	PROPERTIES	Metric	English
Foil Scrim Kraft Backing	120 Micron	4.8 mil	PSTC-133 / ASTM D 3652
Total Thickness (Foil + Adhesive)	170 Micron	6.8 mil	PSTC-133 / ASTM D 3652
Peel Adhesion to Steel	16 N/25mm	57.6 Oz/inch	PSTC-101A / ASTM D3330 A
Rolling Tack (11 mm ball)	5 cm	2 inch	PSTC-6 / ASTM D 3121
Tensile Strength	120 N/25mm	27.3 Lb/In	PSTC-131 / ASTM D 3759
Elongation	1%	1 %	PSTC-131 / ASTM D 3759
Service Temperature	-35 ~ +100°C	-31 ~ + 212 °F	-----
Surface burning characteristics	exceed UL 723 requirements		
Core I.D.	76mm	3"	
Roll width	48mm, 50mm (2"), 60mm, 63mm (2.5"), 72mm, 75mm (3"), 96mm, 100mm (4")		
Roll length	45m (50 yards), 50m		
Jumbo roll size (special sizes of jumbo or log rolls are also available)	1200 mm x 750 – 850 m		

1. The data above are typical results from tests conducted on samples taken from production runs and may be updated without notice. Typical values are not intended to be used for specification development. Tolerance: Technical data $\pm 10\%$; width: $\pm 3\text{mm}$; length: Cut Roll: $\pm 2\%$, Jumbo Roll $\pm 1\%$.
2. The product should be stored in the original packaging material at 20 +/- 5°C and 40-60% relative humidity and protected from direct sunlight, heat and moisture. Shelf life: One year from the date of shipment when stored at the conditions described above.
3. The surface to which the tape is applied must be clean, dry, free of grease and oil and other contaminants and deposits. Recommended temperature of application: 50 – 105 °F (10 – 40 °C).
4. The user is ultimately responsible for determining whether the product is fit for a particular surface and suitable for user's application. No claims will be accepted after product is installed. The user should make necessary tests and trial-application of the tape to confirm suitability for user's special purpose and method of application.
5. Self adhesive tapes are designed for sealing applications only. In the instance when the sides of the joint are subject to mechanical stress, both sides should be securely positioned using appropriate fasteners or hangers prior to the self-adhesive tape application.
6. Calem Technology warranty that the product is free from defects in material and workmanship at the time Calem Technology ships the product. General Terms and Warranty published on the website are also applied to all products. CALEM TECHNOLOGY MAKES NO OTHER WARRANTIES OR CONDITIONS EXPRESSED OR IMPLIED INCLUDING, BUT NOT LIMITED TO FITNESS FOR PARTICULAR PURPOSE, MERCHANTABILITY, ANY IMPLIED WARRANTY ARISING OUT OF CUSTOM OF USAGE OF TRADE AND/OR COURSE OF DEALING. If the product does not conform to this warranty Calem Technology shall, upon notification thereof and substantiation that the product has been stored and applied in accordance with the above requirements, at Calem Technology discretion, replace or credit the product's purchasing price equivalent.
7. Limitation of liability. Since the project specifics, use and application conditions are entirely beyond Calem Technology control, Calem Technology, or reseller(s) of any CT Tape, CT Foil, CT Glass or CT Plast products do not guarantee results from use of any products or other information and expressly deny liability from any possible damage or loss resulting from the use or application of the products. Calem Technology Inc. and seller of the products will not be liable for any loss or damage arising from product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, Sales of goods Act, negligence or strict liability.



1-604-277-6643
186-8120 No. 2 Road
Richmond, BC
V7E 3E6, Canada